



# COUNTERTOP Point-of-Sale

## Big Solutions in a Small Package

Featuring a compact design, the T2 offers all the latest features, including EMV and NFC, and provides high efficiency while taking up minimal counter space.

Designed with the user-experience in mind, the backlit keypad, large keys and color display touchscreen make it easy to use while reducing instances of PIN entry errors.



- **SECURE**  
Meets the highest industry security requirements
- **FUTURE-PROOF**  
EMV & NFC capability that keep you relevant and compliant with today's payment solutions
- **EXPANDABLE**  
Multiple connectivity options, from Ethernet and Dial with optional WiFi

### CERTIFICATIONS



# T2

[www.exadigm.com](http://www.exadigm.com)



## Features & Benefits

**Robust Compliance** - Built-in security transaction engine offers merchants the highest level of secure payment processing.

**NFC Support** - Improves customer experience by offering support for mobile wallet applications. Certified for both PayPass and PayWave.

**EMV Support** - Reinforces your confidence that transactions are secure.

**E-Signature** - Allows you to minimize fraud risk and reduce paper output.

**Premium User Experience** - A color display touchscreen makes viewing transactions easier than ever before.

## Terminal Access Portal (TAP)

ExaDigm's Terminal Access Portal (TAP) provides the fastest, most secure and truly cost-effective remote device management tool for a wide range of users. Featuring a user-friendly interface, TAP can be accessed anytime, anywhere, ensuring real-time device management.

## Specifications

<b>Processor</b>	ARM Cortex-A9, 32-bit secure processor
<b>Memory</b>	256 MB Flash, 128 MB SDRAM
<b>Slots</b>	3 PSAM card slots 1 SD card slot
<b>Card Readers</b>	Contactless - ISO/IEC 14443 Magstripe - 3 track, bi-directional Smart card - ISO 7816
<b>Display</b>	2.8 inch color capacitive screen, 240 x 320
<b>Keypad</b>	10 operational keys, 10 functional keys
<b>Audio</b>	Buzzer
<b>Thermal Printer</b>	58mm x 25m paper roll
<b>Ports</b>	1 USB host 1 Micro USB 1 RS232 1 PIN pad 1 LAN 1 PSTN
<b>PIN Pad</b>	Internal or External (G101), 3DES encryption, DUKPT key management
<b>Communication</b>	Ethernet and Dial, WiFi (optional)
<b>Size</b>	L x W x H = 175 x 81 x 72mm
<b>Weight</b>	320g
<b>Environment</b>	Operating temperature: 0°C to 50°C (32°F to 122°F); storage temperature: -20°C to 60°C (-4°F to 140°F); humidity (non-condense): 5% to 95%
<b>Power Supply</b>	Input: 100-240V, 50-60Hz Output: 8.5V/2.5A
<b>Certifications</b>	PCI PTS 4.0, PA-DSS 3.x, Paywave, Paypass, EMV Level 1 & 2